


8 7 6 5 4 3 2 1



RELEASED  
2013-06-21  
*[Signature]*

- NOTES:**
- 1) MATERIAL: 6061-T6/T6510/T6511 ALUMINUM PER AMS-QQ-A-200/8 (OR AMS 4160) OR ASTM B221  
MINIMUM YIELD TENSILE STRENGTH = 35 ksi  
MINIMUM ULTIMATE TENSILE STRENGTH = 40 ksi  
MINIMUM ELONGATION = 8%  
A SAMPLE FROM EACH BATCH WILL BE PULL TESTED TO ASTM STANDARD B221 BY AN APPROVED TESTING FACILITY TO ENSURE THAT THE BATCH MEETS THE ABOVE MINIMUM MECHANICAL PROPERTIES.
  - 2) FINISH: NONE
  - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
  - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
  - 5) BREAK SHARP EDGES: 0.016 TO 0.025 MAX
  - 6) IDENTIFICATION: IDENTIFY WITH DART P/N AND B/N PER DART QSI 044 6.1
  - 7) WEIGHT: 0.105 lb/in
  - 8) MANUFACTURED USING BON L CANADA DIE # DAA-3
  - 9) NO TOOLING MARKS
  - 10) ORDER AS D2962-XXX WHERE XXX = LENGTH IN INCHES  
EG. 125 LONG: D2962-125

B	UPDATE FORMAT AND EXTRUSION TOLERANCES	SFM	13.05.09
A	NEW ISSUE	RF	00.03.10
REV.	DESCRIPTION	BY	DATE
DESIGN	CP	<b>DART AEROSPACE USA, INC</b> KENT, WA	
DRAWN	SFM		
CHECKED	<i>A.P.</i>	DRAWING NO.	REV. B
MFG. APPR.	<i>[Signature]</i>	D2962	SHEET 1 OF 1
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	EXTRUSION	NTS
DATE	13.05.09	COPYRIGHT © 2000 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	